


TOREN

LED Tri-CCT Surface Mount Garden Bollard Light IP65



- Input voltage: 100-240V 50/60Hz
- Inbuilt Constant Current LED driver
- Housing: powder coated Aluminium
- Diffuser: clear PC
- Mounting plate: Aluminium
- LED chips: 24pcs 2835 SMD
- Tri-CCT (3000K/ 4000K/ 6500K) in one fitting
- CCT switch inside the fitting
- CRI: >80
- Power factor: >0.8
- Ambient temperature: -20 to 50°C
- Not suitable for dimming
- Suitable for 2 way switching
- Suitable for use with sensor



TOREN1
(Dark Grey)

Exterior Lighting



Part No.	Description	Lumens			Watt	Dimensions	PF	Box Weight	Box Size	Carton Qty
		3000K	4000K	6500K						
TOREN1	LED Tri Bollard Light Dark Grey	214M	236LM	211LM	13W	H800xW90xD90mm	0.8	2.0kg	10x10x82cm	1/4

*To avoid disappointment and warranty problems, please ensure the IP rating of the chosen product is relevant for the intended use.

*These bollards are designed for mounting on a solid surface such as a concrete path or sturdy timber decking

- To maintain the IP rating please use circular cable in junction
- For parallel and single connection we recommend using an appropriate IP68 connector (CLA connector recommended).

*Must be installed by a licenced electrician (Installation instructions sheet provided in each product box)